

Bell 412EP

On a Mission.



CAP | Customer
Advantage
Plans



The Bell 412EP is a daily workhorse in the most extreme climates on the planet. Offering an expansive cabin for cargo and/or personnel, dual digital automatic controls and excellent hot & high performance, the Bell 412EP provides multi-mission flexibility to its operators.

STANDARD SPECIFICATIONS

- Seating for 13 passengers and 2 crew in a cabin adaptable for any mission
- Dual Pilot IFR with 3-Axis Dual Digital Automatic Flight Control System, Standard Equipment
- Certified for Single Pilot or Dual Pilot IFR
- Wide opening 7.7 ft/2.32 m doors that accommodate forklift loading into a 220 ft³/6.2 m³ cabin
- Reliable Pratt & Whitney PT6T-3D Twin Pac and proven drive system with 4,000 hour and 5,000 hour TBOs respectively

WORLD-CLASS CUSTOMER SUPPORT AND SERVICE

Every Bell helicopter is backed by around-the-clock, award winning customer support. Bell Helicopter's comprehensive, global service network is rated #1 in the industry. On every continent, in every region, we stand behind each aircraft with the expertise, parts and service needed to meet your mission requirements.



Parapublic



Helicopter Air Ambulance



Corporate



Energy

KEY FEATURES AND BENEFITS

- BLR Strake and FastFin[®] deliver improved hover, cross-wind and hot & high performance while reducing fuel burn
- Safety features including rupture-resistant fuel cells, rugged fuselage and collective mounted throttles
- 28 ft³/0.8m³ baggage space for storage of equipment and supplies
- Adaptability and size to carry up to 13 officers, 6 patients for disaster management or 5,100 lbs/2,313 kg of cargo load

TECHNICAL SPECIFICATIONS

SPEEDS at max gross wt		
V _{NE}	140 kts	259 km/h
Max Cruise	122 kts	226 km/h
Range at V _{LRC} ¹	357 nm	662 km
Max Endurance ¹	3.8 hrs	
CAPACITIES		
Standard Seating	1 + 14	
Maximum Seating	1 + 14	
Standard Fuel	331 US gal	1,251 liters
Aux Fuel	33 or 163 US gal	123 or 617 liters
Cabin Volume	220 ft ³	6.2 m ³
Baggage Compartment Volume	28 ft ³	0.8 m ³
WEIGHTS		
Empty Weight (Base Aircraft)	6,800 lbs	3,084 kg
Useful Load (Internal, Base Aircraft)	5,100 lbs	2,313 kg
Max Gross Weight (Internal)	11,900 lbs	5,398 kg
Max Gross Weight (External)	11,900 lbs	5,398 kg
Cargo Hook Capacity	4,500 lbs	2,041 kg

¹ Max GW, ISA, Std fuel – no reserves at sea level

BELLHELICOPTER.COM



© 2017 Bell Helicopter Textron Inc. All registered trademarks are the property of their respective owners. The information herein is general in nature and may vary with conditions. Individuals using this information must exercise their independent judgment in evaluating product selection and determining product appropriateness for their particular purpose and requirements. For performance data and operating limitations for any specific mission, reference must be made to the approved flight manual. Bell Helicopter Textron Inc. makes no representations or warranties, either expressed or implied, including without limitation any warranties of merchantability or fitness for a particular purpose with respect to the information set forth herein or the product(s) and service(s) to which the information refers. Accordingly, Bell Helicopter Textron Inc. will not be responsible for damages (of any kind or nature, including incidental, direct, indirect, or consequential damages) resulting from the use of or reliance on this information. Bell Helicopter Textron Inc. reserves the right to change product designs and specifications without notice. 412EP TEFS 150116-R02 EN

On a Mission.

