

Bell Huey II

On a Mission.





From law enforcement air support to troop/SWAT insertion and extraction, the Bell Huey II provides the flexible, economical, high performance medium helicopter solution backed by the best support network in the world.

STANDARD SPECIFICATIONS

- Increased power to 1800 shp/1342 kW with the T53-L-703 upgrade package
- New main and tail rotor hub assemblies and blades
- 13 place seating in an exceptionally wide cabin
- Large sliding doors
- 5,000 lbs/2,268 kg cargo lifting capability
- Useful load of 4,873 lbs/2,210 kg

WORLD-CLASS CUSTOMER SUPPORT AND SERVICE

Every Bell helicopter is backed by around-the-clock, award winning customer support. Bell Helicopter's comprehensive, global service network is rated #1 in the industry. On every continent, in every region, we stand behind each aircraft with the expertise, parts and service needed to meet your mission requirements.

KEY FEATURES AND BENEFITS

- Dedicated OEM Support
- Low life-cycle cost
- Nearly zero-time aircraft/re-manufactured/new components
- Customized to fit your mission
- Wide windscreen provides excellent visibility for SAR operations
- Accommodates a wide array of instrumentation and avionics
- Multiple crew positions and litter configurations

TECHNICAL SPECIFICATIONS

SPEEDS at max gross wt		
V _{NE}	111 kts	206 km/h
Max Cruise	106 kts	196 km/h
Range at V _{LRC} ¹	246 nm	455 km
Max Endurance ¹	2.6 hrs	
CAPACITIES		
Standard Seating	1 + 12	
Maximum Seating	1 + 14	
Standard Fuel	211 US gal	799 liters
Aux Fuel (Optional)	150 US gal	568 liters
Cabin Volume	220 ft ³	6.2 m ³
WEIGHTS		
Empty Weight (Standard Configuration)	5,627 lbs	2,552 kg
Useful Load, (Internal, Standard Configuration)	4,873 lbs	2,210 kg
Max Gross Weight (Internal)	10,500 lbs	4,763 kg
Max Gross Weight (External)	11,200 lbs	5,080 kg
Cargo Hook Capacity	5,000 lbs	2,268 kg

¹ Max GW, ISA, Std fuel – no reserves at sea level



Parapublic



Helicopter Air Ambulance



Troop Transport & Insertion



Search & Rescue

BELLHELICOPTER.COM



© 2015 Bell Helicopter Textron Inc. All registered trademarks are the property of their respective owners. The information herein is general in nature and may vary with conditions. Individuals using this information must exercise their independent judgment in evaluating product selection and determining product appropriateness for their particular purpose and requirements. For performance data and operating limitations for any specific mission, reference must be made to the approved flight manual. Bell Helicopter Textron Inc. makes no representations or warranties, either expressed or implied, including without limitation any warranties of merchantability or fitness for a particular purpose with respect to the information set forth herein or the product(s) and service(s) to which the information refers. Accordingly, Bell Helicopter Textron Inc. will not be responsible for damages (of any kind or nature, including incidental, direct, indirect, or consequential damages) resulting from the use of or reliance on this information. Bell Helicopter Textron Inc. reserves the right to change product designs and specifications without notice. Huey II TEFS 150116-R00 EN

On a Mission.

